



Product Description:

IB Polymer Batten Bar is made of corrosion resistant polymer. All ends have been rounded and edges have been deburred. Holes are punched into each bar with a standard-spacing of 3" oc. Spacing holes at 12" oc. are also marked for ease of identification.

Size/Features:

Dimensions: 1/20" thick x 1" wide

Length: 250'

Holes: 1/4" flat

Spacing: 3" o.c.

Packaging:

IB Polymer Batten Bars are sold individually in 250-foot coil units and are shipped in a cardboard box. Max 1 unit per box.

Weight:

10 lbs. per unit

Installation:

IB Polymer Batten Bar is designed to secure IB TPO and IB PVC membranes to steel, wood, and concrete decks using the appropriate IB Fastener.



Product details stated are nominal as manufactured, and the results of tests and/or calculations and therefore are non-binding and do not represent a guarantee or warranted characteristics. User and/or designer are responsible for confirming suitable performance for specific application and conforming with all applicable laws and regulations.

Go to <https://ibroof.com/tds> for the most up-to-date version of this document.

Toll Free: 800-426-1626

Care has been taken to ensure that the contents of this publication are accurate, however IB Roof Systems and any subsidiary companies do not accept responsibility for errors or for information that is found to be misleading. Suggestions for, or description of, the end use of application of products or methods of working, are for information only and IB Roof systems and any subsidiary accept no responsibility in respect thereof.



Quality Products



Exceptional Service



Technical Expertise

IBroof.com

510810017 1/23/2026