



Product Description:

Fabricated from 24-gauge, ASTM A653-09, CS Type B, G90 galvanized sheet metal with a durable 45-mil non-reinforced IB PVC film with acrylic finish laminated to the top surface. Made to exact specification and finished with factory welded, non-reinforced 60-mil PVC target flashing.

2" wide bar with a hemmed caulk lip on the top and a hemmed bottom edge.

Features:

- Durable 45-mil IB PVC non-reinforced film laminated to corrosion resistant 24-gauge, G90 galvanized metal
- Acrylic finish top surface

Flexible Installation

- On top of membrane at vertical surfaces
- Underneath the roofing membrane to allow for direct welding to the term bar for a cleaner application

Sizes:

2" wide x 10' long

Packaging:

IB® Clad Termination Bar are sold individually in 10-foot pieces and are shipped in a 10' cardboard box. Max 50 units per tube.

Weight:

3.0 lbs. per piece; 150 lbs. per 50-unit tube

Available Colors:

			
White	Bronze	Tan	Gray

Also available in 24-gauge Clad SAE 304 stainless steel (White only)

Application:

Refer to IB Specifications and Construction Details for additional installation requirements.

- Secure termination bar to the wall with approved IB® Fasteners suitable for the substrate spaced
- No more than 6" o.c. for most applications.

Note: Maximum warranty term limited to twenty (20) years when used to terminate flashing without a metal counter flashing.



Product details stated are nominal as manufactured, and the results of tests and/or calculations and therefore are non-binding and do not represent a guarantee or warranted characteristics. User and/or designer are responsible for confirming suitable performance for specific application and conforming with all applicable laws and regulations.

Go to <https://ibroof.com/tds> for the most up-to-date version of this document.

Toll Free: 800-426-1626

Care has been taken to ensure that the contents of this publication are accurate, however IB Roof Systems and any subsidiary companies do not accept responsibility for errors or for information that is found to be misleading. Suggestions for, or description of, the end use of application of products or methods of working, are for information only and IB Roof systems and any subsidiary accept no responsibility in respect thereof.



Quality Products



Exceptional Service



Technical Expertise

IBroof.com

510810021 V.1 7/20/26