



Product Description:

Made from 24-gauge, SAE 304 stainless steel sheet metal with a durable 45-mil non-reinforced IB PVC film with acrylic finish, laminated to the top surface with a standard metal drip edge profile.

Features:

- Factory fabricated edge metal ready to install onsite
- Acrylic finish top surface
- Open hem kick-out provides a corrosion resistant, heat weldable perimeter roof edge termination
- Additional sizes and profiles available through custom order to your specifications

Sizes:

Standard sizes available in 2.5" and 4" drip edge.
Custom sizes are available as a special order.

Packaging:

Sold per 10' section
Available in 100-piece/box

Available Clad Metal Colors:

Standard Clad Finish for SAE 304 stainless steel in White.



Special Order in Bronze, Tan, & Gray



Accessory Metal Cleat:

- Factory fabricated 22-gauge ASAE 304 stainless steel cleats are sold separately
- Custom manufactured for use for installations requiring a continuous cleat.
- Formed to profile with a 1/2" deck flange



	DRIP EDGE	2.5"	4"
A - FLANGE		3"	3.5"
B - COVERAGE		2"	3.5"
C - FACE		2.5"	4.75"
D - HEM		.50"	.50"
LENGTH		10'	10'
WEIGHT		5.5 LBS	7.5 LBS

ANSI/SPRI ES-1 Tested Metals (Report #103942901MID-001R0)		
Product ID	Attachment	Max. Load / Max. Design Pressure*
2.5" Clad Drip Edge Stainless Steel Metal with 22 ga. stainless steel cleat	Min. 1-1/2" smooth shank roofing nail 6" o.c.; or IB HD #14 Fastener 12" o.c. Min. penetration 1-1/2" into nailer/substrate	550 lbs / 225 MDP
4" Clad Drip Edge Stainless Steel Metal with 22 ga. stainless steel cleat	Min. 1-1/2" smooth shank roofing nail 6" o.c.; or IB HD #14 Fastener 12" o.c. Min. penetration 1-1/2" into nailer/substrate	550 lbs / 225 MDP
*Reflects safety factor of 2 applied. Building owner, project designer, engineer, or contractor is responsible to determine appropriate safety factor for project design conditions.		

Product details stated are nominal as manufactured, and the results of tests and/or calculations and therefore are non-binding and do not represent a guarantee or warranted characteristics. User and/or designer are responsible for confirming suitable performance for specific application and conforming with all applicable laws and regulations.

Go to <https://ibroof.com/tds> for the most up-to-date version of this document.

Toll Free: 800-426-1626

Care has been taken to ensure that the contents of this publication are accurate, however IB Roof Systems and any subsidiary companies do not accept responsibility for errors or for information that is found to be misleading. Suggestions for, or description of, the end use of application of products or methods of working, are for information only and IB Roof systems and any subsidiary accept no responsibility in respect thereof.