



Product Description:

Fabricated with a 24-gauge, G90 coated galvanized sheet metal with a durable 45-mil non-reinforced IB PVC film with acrylic finish, laminated to the top surface formed into a standard metal drip edge profile.

Features:

- Factory fabricated edge metal ready to install onsite
- Acrylic finish top surface
- Open hem kick-out provides a corrosion resistant, heat weldable perimeter roof edge termination.
- Custom sizes are available as a special order.

Sizes:

Standard sizes available in 2.5" and 4" drip edge.

Packaging:

Sold per 10' section
Available in 100-piece/box

Available Colors:

Standard Clad Finish in White, Bronze, Tan, and Gray

White	Bronze	Gray	Tan

Accessory Metal Cleat:

- Factory fabricated 22-gauge ASTM G53-09, CS Type B, G90 galvanized steel cleats are sold separately
- Custom manufactured for use with IB® Clad Gravel Stop produced for installations requiring a continuous cleat.
- Formed to profile with a 1/2" deck flange

Warranty:

Maximum warranty term limited to twenty (20) years when galvanized clad metal is used.

For eligible warranty terms greater than twenty years refer to Stainless Steel-Clad finish profiles or IB® Drip Edge Flashing.



	DRIP EDGE	2.5"	4"
A - FLANGE		3"	3"
B - COVERAGE		2"	3.5"
C - FACE		2.5"	4"
D - HEM		.50"	.50"
LENGTH		10'	10'
WEIGHT		5.5 LBS	7.5 LBS

ANSI/SPRI ES-1 Tested Metals (Report #103942901MID-001R0)

Product ID	Attachment	Max. Load / Max. Design Pressure*
2.5" Clad Drip Edge Metal with CS Steel G90 22 ga. cleat	Min. 1-1/2" smooth shank roofing nail 6" o.c.; or IB HD #14 Fastener 12" o.c. Min. penetration 1-1/2" into nailer/substrate	550 lbs / 225 MDP
4" Clad Drip Edge Metal with G90 CS Steel 22 ga. cleat	Min. 1-1/2" smooth shank roofing nail 6" o.c.; or IB HD #14 Fastener 12" o.c. Min. penetration 1-1/2" into nailer/substrate	550 lbs / 225 MDP

*Reflects safety factor of 2 applied. Building owner, project designer, engineer, or contractor is responsible to determine appropriate safety factor for project design conditions.

Product details stated are nominal as manufactured, and the results of tests and/or calculations and therefore are non-binding and do not represent a guarantee or warranted characteristics. User and/or designer are responsible for confirming suitable performance for specific application and conforming with all applicable laws and regulations.

Go to <https://ibroof.com/tds> for the most up-to-date version of this document.

Toll Free: 800-426-1626

Care has been taken to ensure that the contents of this publication are accurate, however IB Roof Systems and any subsidiary companies do not accept responsibility for errors or for information that is found to be misleading. Suggestions for, or description of, the end use of application of products or methods of working, are for information only and IB Roof systems and any subsidiary accept no responsibility in respect thereof.