



Product Description:

Designed to terminate Single-Ply membrane to parapet walls and other penetrations.

Features:

- IB® Aluminum Termination Bar is made of extruded aluminum
- Oval holes are punched into each bar, with a standard spacing of 6" on center (o.c.)
- Corrosion coating:15/15 Kesternich per FM 4470

Size:

1" wide x 10' long

Product Properties:

- Dimensions: .082" thick x 1" wide
- Holes: .280" x .380" slotted
- Material: 6063-T6 Extruded Aluminum



Product details stated are nominal as manufactured, and the results of tests and/or calculations and therefore are non-binding and do not represent a guarantee or warranted characteristics. User and/or designer are responsible for confirming suitable performance for specific application and conforming with all applicable laws and regulations.

Weight:

- 1 lbs. per unit, 50 lbs. per 50-unit tube
- Corrosion coating:15/15 Kesternich per FM 4470

Packaging:

Sold individually in 10-foot pieces and are shipped in a 10' cardboard box. Max 50 units per tube.

Warranty:

Maximum warranty term limited to twenty (20) years when used to terminate flashing without a metal counter flashing.

Go to <https://ibroof.com/tds> for the most up-to-date version of this document.

Toll Free: 800-426-1626

Caution: Care has been taken to ensure that the contents of this publication are accurate, however IB Roof Systems and any subsidiary companies do not accept responsibility for errors or for information that is found to be misleading. Suggestions for, or description of, the end use of application of products or methods of working, are for information only and IB Roof Systems and any subsidiary accept no responsibility in respect thereof.



Quality Products



Exceptional Service



Technical Expertise

IBroof.com

510810029 1/28/2026