

## Product Description:

IB Cover Strip is made from IB PVC Single Ply, comprised of a polyester scrim reinforced, compounded PVC resin-based sheet with plasticizers, stabilizers, fillers, pigments, and other proprietary materials meeting ASTM D4434, Type III. Rolls are manufactured in nominal 60-mil thicknesses and use an anti-wicking scrim for added strength, tear resistance and enhanced moisture resistance.

## Thickness:

- 60 mil

## Sizes:

- 6" x 90' / 18.0 lbs. | 12" x 90' / 36.1 lbs.

## Packaging:

Sold in individual shrink-wrapped rolls.

## Use:

- Stripping in IB Clad Metal Drip Edge, IB Clad Gravel Stop, and clad metal flashings
- As a cover strip over mechanically fastened batten bars, over intermediate termination bars or fastener rows on walls, and over supplemental exposed fastening rows at perimeter and corner roof zones
- Stripping in IB PVC Single Ply FB end laps
- Seam repair

## Application:









Refer to IB Specifications and Construction Details for installation requirements and additional information for specific uses. IB Cover Strip is designed for hot air welded seaming and installation over approved IB PVC Single Ply membranes.

## Approvals:

IB PVC membranes are listed with various component assemblies at UL and Factory Mutual (F.M. Global) for fire, wind uplift, impact, and chemical resistance. Visit our website for links to these agencies and listings at: [www.ibroof.com](http://www.ibroof.com).



## Available Colors:

			
White	Cool Sand	Cool Stone	ChemGuard
			
Bronze	Gray	Tan	Terra Cotta

Product details stated are nominal as manufactured, and the results of tests and/or calculations and therefore are non-binding and do not represent a guarantee or warranted characteristics. User and/or designer are responsible for confirming suitable performance for specific application and conforming with all applicable laws and regulations.