

Product Description:

IB® Clad Termination Bar is fabricated from 24-gauge, ASTM A653-09, CS Type B, G90 galvanized sheet metal with a durable 45-mil non-reinforced IB PVC film with acrylic finish laminated to the top surface. Bars are 2" wide with a hemmed caulk lip on the top and a hemmed bottom edge and can be installed over membrane flashings at vertical surfaces (like a traditional termination bar) or installed first to allow for the membrane to be welded directly to the IB® Clad Termination Bar for a cleaner application.

Sizes:

2" wide x 10' long

Colors:

White, Bronze, Tan, and Gray



Also available in 24-gauge Clad SAE 304 stainless steel (White only)



Packaging:

IB® Clad Termination Bar are sold individually in 10-foot pieces and are shipped in a 10' cardboard box. Max 50 units per tube.

Weight:

- 3.0 lbs. per piece; 150 lbs. per 50-unit tube

Features:

- Durable 45-mil IB PVC non-reinforced film laminated to corrosion resistant 24-gauge, G90 galvanized metal
- Acrylic finish top surface
- Installed either on top or underneath the roofing membrane

Installation:

Refer to IB Specifications and Construction Details for additional installation requirements. Secure termination bar to the wall with approved IB® Fasteners suitable for the substrate spaced no more than 6" o.c. for most applications.

Note: Maximum warranty term limited to twenty (20) years when used to terminate flashing without a metal counter flashing.

Front



Back



Product details stated are nominal as manufactured, and the results of tests and/or calculations and therefore are non-binding and do not represent a guarantee or warranted characteristics. User and/or designer are responsible for confirming suitable performance for specific application and conforming with all applicable laws and regulations.