



Product Description:

IB TPO HW/SA Cover Tape is made from 60 mil reinforced thermoplastic polyolefin, (TPO) membrane laminated to a 3" wide x 30 mil thick, self-adhesive tape.

Use:

- As a strip in flashing detail for metal edge flanges
- Used in conjunction with IB TPO Primer
- Max system warranty limitation term is 25 years.

Thickness:

- 60 mil – membrane
- 30 mil – tape

Available Colors:



Sizes:

6" x 50' / 1.0 lbs.

Packaging:

Each box contains two (2) individual rolls.

Storage:

Store IB TPO HW/SA Cover Tape indoors, out of direct sunlight, in temperatures between 60°F – 80°F (16°C – 27°C) in original unopened containers and away from objects that could cause physical damage or create punctures as well as ignition sources. The membrane is flammable and will catch fire when exposed to open flame.



Product details stated are nominal as manufactured, and the results of tests and/or calculations and therefore are non-binding and do not represent a guarantee or warranted characteristics. User and/or designer are responsible for confirming suitable performance for specific application and conforming with all applicable laws and regulations.

Application:

Refer to IB TPO Specifications and Construction Details for installation requirements and additional information for specific uses. Prime metal with IB TPO Primer prior to applying IB TPO HW/SA Cover Tape. IB TPO HW/SA Cover Tape is designed to be self-adhered to the metal edge flanges and hot air welded over approved IB TPO SM and IB TPO FB membranes.

Refer to www.ibroof.com for additional installation instructions. Membranes must not be applied during adverse weather or without precautionary measures in temperatures below 40°F (4°C). All surfaces should be clean, dry, free of dirt, dust, debris, oils, soaps, coatings, and other contaminants that may inhibit bonding.

Self-Life:

18 months from date of manufacture

Safety Precautions:

Use proper equipment and assistance when moving, lifting, handling, or transporting membrane rolls to avoid personal injuries as well as damage to the membrane. Refer to the Product Safety Data Sheet for additional safety information.

Go to <https://ibroof.com/tds> for the most up-to-date version of this document.

Toll Free: 800-426-1626

Care has been taken to ensure that the contents of this publication are accurate, however IB Roof Systems and any subsidiary companies do not accept responsibility for errors or for information that is found to be misleading. Suggestions for, or description of, the end use of application of products or methods of working, are for information only and IB Roof systems and any subsidiary accept no responsibility in respect thereof.