



Product Description:

IB TPO Termination Tape is made from 45 mil reinforced thermoplastic polyolefin, (TPO) membrane laminated to a 3" wide x 30 mil thick, self-adhesive tape.

Use:

- To secure the field membrane at any angle change greater than 2 in/ft.
- Used in lieu of fastening through the field membrane with screws and plates at angle changes.
- Used in conjunction with IB TPO Primer
- Must be both self-adhered and mechanically fastened to properly function.

Thickness:

- 45 mil – membrane
- 30 mil – tape

Available Colors:



White

Packaging:

Each box contains two (2) individual rolls

Application:

Refer to IB TPO Specifications and Construction Details for installation requirements and additional information for specific uses. Prior to application, use the IB TPO Cleaner to ensure no oil, dirt, moisture, or other foreign materials are present on the applied surfaces that could damage the TPO Reinforced Termination Strip. Unroll the IB TPO Termination Tape adjacent to the curb, wall, or rooftop transition change with the tape portion positioned farthest point from the transition point and with the release liner facing up. Use IB XHD #15 Fasteners and IB 2-3/8" Barbed Seam Plates or other fastener/plate as appropriate for deck type, (installed 12" o.c.) to anchor the IB TPO Termination Tape through the reinforced membrane half of the termination tape, which is closest to the transition. Position the IB TPO SM membrane over the termination tape, with the release liner still intact, and allow the membrane to relax. Fold the TPO membrane back exposing the tape. Use the IB TPO Primer to prime the TPO membrane that will be applied over the termination tape side and wait for the primer to flash off. Remove the release liner from the tape and slowly move the IB TPO SM membrane onto the tape working the sheet into place to avoid wrinkles. Apply IB TPO Bonding Adhesive, IB TPO LVOC Adhesive, or IB TPO Spray Contact Adhesive to both the back of the membrane, the membrane half of



Product details stated are nominal as manufactured, and the results of tests and/or calculations and therefore are non-binding and do not represent a guarantee or warranted characteristics. User and/or designer are responsible for confirming suitable performance for specific application and conforming with all applicable laws and regulations.

the termination tape, and the surface on the curb, wall, or rooftop transition that will mate with the membrane. Allow the adhesive to flash off. Once the adhesive has flashed off, slowly roll the IB TPO SM membrane into place against the membrane half of the termination strip and the surface on the transition to mate with the membrane. Use a hand roller to ensure strong adhesion between the TPO membrane and the mating surfaces. Roll until all surfaces are smooth against the receiving substrates.

Refer to www.ibroof.com for additional installation instructions. Membranes must not be applied during adverse weather or without precautionary measures in temperatures below 40°F (4°C). All surfaces should be clean, dry, free of dirt, dust, debris, oils, soaps, coatings, and other contaminants that may inhibit bonding.

Storage:

Store IB TPO Termination Tape indoors, out of direct sunlight, in temperatures between 60°F – 80°F (16°C – 27°C) in original unopened containers and away from objects that could cause physical damage or create punctures as well as ignition sources. The membrane is flammable and will catch fire when exposed to open flame.

Self-Life:

18 months from date of manufacture

Safety Precautions:

Use proper equipment and assistance when moving, lifting, handling, or transporting membrane rolls to avoid personal injuries as well as damage to the membrane. Refer to the Product Safety Data Sheet for additional safety information.

Go to <https://ibroof.com/tds> for the most up-to-date version of this document.

Toll Free: 800-426-1626

Caution has been taken to ensure that the contents of this publication are accurate, however IB Roof Systems and any subsidiary companies do not accept responsibility for errors or for information that is found to be misleading. Suggestions for, or description of, the end use of application of products or methods of working, are for information only and IB Roof Systems and any subsidiary accept no responsibility in respect thereof.



Quality Products



Exceptional Service



Technical Expertise

IBroof.com

510910028 1/16/2026