



## Product Description:

IB TPO Recover Membrane Vent is a two-way style HPDE vent with a strong cap that is permanently attached. The 5" vent has an IB TPO target flashing applied to the flange. The vent eliminates field fabrication, installs in minutes and requires no fasteners.

## Use:

Install in accordance with IB Specifications and Construction Details at the rate of 1 for every 1,000 sq. ft. on all mechanically attached assemblies and when recovering over existing insulated roof systems and existing lightweight concrete decks.

**Note: Not intended for interior space or general building ventilation. Do not use over or in lieu of other roof vents, exhaust, plumbing, bath, or kitchen vents.**

## Thickness:

60 mil

## Available Membrane Colors:



*\*Gray and tan are special order only*

## Available Vent Colors:



## Application:

Refer to IB TPO Specifications and Construction Details for installation requirements and additional information for specific uses.

1. Place IB TPO Recover Membrane Vent over vent hole in the roof deck.
2. Heat weld TPO membrane flange over approved IB TPO SM and IB TPO FB membranes.
3. Apply IB TPO Cut Edge Sealant around edge of flange.

Refer to [www.ibroof.com](http://www.ibroof.com) for additional installation instructions. Membranes must not be applied during adverse weather or without precautionary measures in temperatures below 40°F (4°C). All surfaces should be clean, dry, free of dirt, dust, debris, oils, soaps, coatings, and other contaminants that may inhibit bonding.



Product details stated are nominal as manufactured, and the results of tests and/or calculations and therefore are non-binding and do not represent a guarantee or warranted characteristics. User and/or designer are responsible for confirming suitable performance for specific application and conforming with all applicable laws and regulations.

Go to <https://ibroof.com/tds> for the most up-to-date version of this document.

Toll Free: 800-426-1626

Care has been taken to ensure that the contents of this publication are accurate, however IB Roof Systems and any subsidiary companies do not accept responsibility for errors or for information that is found to be misleading. Suggestions for, or description of, the end use of application of products or methods of working, are for information only and IB Roof systems and any subsidiary accept no responsibility in respect thereof.