



Product Description:

IB TPO T-Top Roof Vents are prefabricated exhaust vents used for non-heated exhaust ventilation. IB TPO T-Top Roof Vents are designed for single ply low slope roofing systems. The vent eliminates field fabrication, installs in minutes and has a removable top for easy maintenance. IB TPO T-Top hood is made of SMP painted steel, closely matching the color of the TPO, and is designed with ends or “ears.” Includes a reinforced TPO Single Ply target flashing with a 3-inch weldable flange.

Use:

- Ready to install, eliminating field fabrication
- Designed to effectively block wind while allowing non-heated exhaust ventilation
- 1/8” galvanized wire mesh internal screens keep insects and debris out of ventilated areas
- Removable top
- **Note:** IB TPO T-Top Roof Vent Flashings are not intended to function in dryer exhaust applications or moisture relief vent applications.

Thickness:

60 mil

Available Colors:



*Gray and tan are special order only

Sizes & Packaging:

Size	Box Qty	Box Wt.	NFA
4"	6	8 lbs.	12 lbs.
6"	4	10 lbs.	25 lbs.
8"	2	12 lbs.	44 lbs.

Storage:

Store IB TPO T-Top Roof Vent Flashing indoors, out of direct sunlight, in original unopened containers and away from objects that could cause physical damage or create punctures as well as ignition sources. The membrane is flammable and will catch fire when exposed to open flame.

Safety Precautions:

Use proper equipment and assistance when moving, lifting, handling, or transporting membrane rolls to avoid personal injuries as well as damage to the membrane. Refer to the Product Safety Data Sheet for additional safety information.



Product details stated are nominal as manufactured, and the results of tests and/or calculations and therefore are non-binding and do not represent a guarantee or warranted characteristics. User and/or designer are responsible for confirming suitable performance for specific application and conforming with all applicable laws and regulations.

Application:

Refer to IB TPO Specifications and Construction Details for installation requirements and additional information for specific uses.

1. Place appropriately sized IB TPO T-Top Roof Vent over vent hole in the roof deck.
2. Lift membrane flange and fasten sub-base to deck using appropriate IB Fasteners approved for the substrate type.
3. Heat weld TPO membrane flange over approved IB TPO SM and IB TPO FB membranes.
4. Apply IB TPO Cut Edge Sealant around edge of flange.

Refer to www.ibroof.com for additional installation instructions. Membranes must not be applied during adverse weather or without precautionary measures in temperatures below 40°F (4°C). All surfaces should be clean, dry, free of dirt, dust, debris, oils, soaps, coatings, and other contaminants that may inhibit bonding.

Go to <https://ibroof.com/tds> for the most up-to-date version of this document.

Toll Free: 800-426-1626

Care has been taken to ensure that the contents of this publication are accurate, however IB Roof Systems and any subsidiary companies do not accept responsibility for errors or for information that is found to be misleading. Suggestions for, or description of, the end use of application of products or methods of working, are for information only and IB Roof systems and any subsidiary accept no responsibility in respect thereof.