



## Product Description:

IB Membrane Cleaner is a low VOC universal cleaning agent designed to remove foreign contaminants from the TPO, PVC, KEE, and EPDM membranes surface prior to welding or mating application. VOC compliant including SCAQMD Rule 1171 for solvent cleaners.

## Use:

- For removal of asphalts, soils, soaps, and other contaminants.
- Apply with a cloth rag

## Packaging:

F-Style Metal Can - 1 gal	4 cans/case
7 lbs/gallon	

## Color:

Clear

## Temperature Guidelines/Storage & Handling:

Store in a dry area, indoors, out of direct sunlight in the original unopened container.

**Optimum product storage temperature:** 40-90°F (4-32°C) for 24 hours prior to use.

Internal Chemical Temperature at Application: Warm or cool product temperature to 60-80°F/15-27°C prior to use.

**Outside Application Temperature:** Ambient is 40°F (4°C) and rising.

**Note:** Extended exposure to temperatures outside this range may reduce shelf life. Protect from freezing.

Physical Properties	
VOC	25 g/L (EPA Method 24)
Shelf Life	12 months from date of manufacture

## Limitations:

- Do not use when ambient, substrate or product temperatures are outside specified temperature ranges.
- Do not use during inclement weather, on wet surfaces or on any substrate showing signs of deterioration or loss of structural integrity.
- Protect from freezing.



Product details stated are nominal as manufactured, and the results of tests and/or calculations and therefore are non-binding and do not represent a guarantee or warranted characteristics. User and/or designer are responsible for confirming suitable performance for specific application and conforming with all applicable laws and regulations.

- Do not thin.
- Do not use after the expiration date.

## Safety:

**Caution:** Product should be used only in well-ventilated areas. It may cause eye, skin and respiratory irritation, and is harmful or fatal if swallowed. Avoid contact with skin. Use impervious clothing and rubber gloves to avoid prolonged or repeated contact with skin. Product may settle during transport or storage. Shake the container thoroughly before use. Do not mix with electric or spark-producing equipment due to the risk of flash fire. Reach the container label and follow all safety instructions.

## Application:

Refer to IB TPO Specifications and Construction Details for additional installation instructions.

- IB Membrane Cleaner should be applied to a structurally sound substrate that is clean, dry, free of frost, oils, soaps, silicone, or loose material that may inhibit bonding.
- Membranes and flashings that have been exposed to the elements or weather conditions greater than seven (7) days must be properly cleaned with IB Membrane Cleaner prior to welding or receiving self-adhesive applications.
- Membrane cleaning during roof construction is typically unnecessary when laps and seams are completed before the close of each day, and the work area is kept clean and free of debris.
- Dust, tear-off debris, trafficked surface contaminants and



adhesive residues should be kept from the membrane surface and particularly avoided within critical lap and seam areas.

- Laps which cannot be completed by the close of day or that exhibit evidence of moisture or condensation must be cleaned and prepared in accordance with IB cleaning instructions.
- Contamination of the roof surface and within seam areas can be encountered during installation, repair, and long-term maintenance of the roof. Wipe all surfaces, including within lap areas as necessary, with a clean dry cloth to remove any loose dirt, debris, or moisture. Follow with a dampened cloth using a small amount of IB Membrane Cleaner applied to the rag only.
- Finish with a dry clean cloth and allow it to completely dry.
- Apply IB Membrane Cleaner to a cloth rag and apply.

Note: The use of degreasers is not permitted, which can leave a film residue.

Refer to [www.ibroof.com](http://www.ibroof.com) for additional installation instructions.

Go to <https://ibroof.com/tds> for the most up-to-date version of this document.

Toll Free: 800-426-1626

Care has been taken to ensure that the contents of this publication are accurate, however IB Roof Systems and any subsidiary companies do not accept responsibility for errors or for information that is found to be misleading. Suggestions for, or description of, the end use of application of products or methods of working, are for information only and IB Roof systems and any subsidiary accept no responsibility in respect thereof.