

IB TPO Product Selection Guide

TPO Membranes

Product	Description	System Type ¹	Color Options*	Warranty Eligibility ²	Size / Unit
IB TPO 60 SM Membrane	60-mil, weft-inserted polyester scrim, smooth backed thermoplastic polyolefin (TPO) single ply membrane, meets all requirements of ASTM D6878.	FA, IW, MA	White, Gray, Tan	10, 15, 20	5' x 100' 6' x 100' 8' x 100' 10' x 100' 12' x 100'
IB TPO 80 SM Membrane	80-mil, weft-inserted polyester scrim, smooth backed thermoplastic polyolefin (TPO) single ply membrane, meets all requirements of ASTM D6878.	FA, IW, MA	White, Gray, Tan	10, 15, 20, 25	5' x 100' 6' x 100' 8' x 100' 10' x 100' 12' x 100'
IB TPO 115 FB Membrane	115-mil, weft-inserted polyester scrim, thermoplastic polyolefin (TPO) single ply membrane, with an integral polyester fleece backing. Meets all requirements of ASTM D6878.	FA, MA	White	10, 15, 20	10' x 100'
IB TPO 135 FB Membrane	135-mil, weft-inserted polyester scrim, thermoplastic polyolefin (TPO) single ply membrane, with an integral polyester fleece backing. Meets all requirements of ASTM D6878.	FA, MA	White	10, 15, 20, 25	10' x 50'

¹MA: Mechanically Attached, FA: Adhered, IW: Induction Weld

²Total Systems Warranty (NDL), Commercial Limited Material Warranty, and Warranty Plus Limited Labor & Material Warranty

*Gray and Tan Colors are Special Order and require lead times.

TPO Membrane Accessories

Product	Description	Use	Size / Unit
IB TPO Cover Strip	60-mil, reinforced TPO membrane, available in White, Gray, and Tan	Used to strip in metal edge flanges and perimeter / corner zone flashing in MA assemblies	8" x 50'
IB TPO HW/SA Cover Tape	60-mil, reinforced TPO membrane laminated, to a 3" x 30-mil self-adhesive tape. Available in White only.	Used to strip in metal edge flanges with one half a self-adhesive TPO and the other half a heat weldable TPO detail	6" x 50'
IB TPO SA Cover Tape	30-mil, non-reinforced TPO self-adhering, cover tape. Available in White only.	Self-adhesive TPO membrane used to strip-in metal flanges.	6" x 100'
IB TPO Termination Tape	45-mil, reinforced TPO membrane laminated, on half of the width of the strip, to a 3" x 30-mil self-adhesive tape. Available in White only.	Used to terminate TPO SM membranes at any angle change greater than 2" per foot without having to terminate through the membrane with fasteners and termination bar.	6" x 100'
IB TPO SA Yellow Safety Tape	30-mil, non-reinforced, TPO laminated to a 25-mil self-adhesive tape. Available in Safety Yellow only	Used as a visual and physical safety warning designation on roof areas including areas of caution and potential life safety hazards.	5.5" x 100'
IB TPO Walk Tread	120-mil textured non-reinforced TPO walk way pad. Available in Grey and Safety Yellow	Used as membrane protection in high traffic / maintenance areas	30" x 50'
IB TPO NR Detail Roll	60-mil, non-reinforced TPO detail flashing membrane. Available in White, Gray, and Tan	Used at critical areas like canted corners, field wrapped penetrations, etc.	24" x 50'
			48" x 50'
IB TPO T-Joint Patch	Flexible, non-reinforced TPO. Available in White, Gray, and Tan	Generally used to reinforce T-joints. May be used to patch punctures.	4" dia.
IB TPO Pre-molded Corner	60-mil pre-molded accessory designed for use as an inside corner or outside corner. Available in White only	Designed for use as an inside corner or outside corner on all TPO thermoplastic roof systems.	6" x 6" x 3"
IB TPO Universal Corner	60-mil irregular corner flashings available in White, Gray, Tan colors	Ideal for use on canted or irregular outside corner flashing conditions	6" dia.
IB TPO Pipe Flashing	TPO cone flashing with a preformed flange. Comes with clamping ring. Available in White, Gray, Tan colors	Heat weldable TPO flashing of penetrations of 1"-6" diameters such as pipes, conduit, gas lines, etc.	6"
IB TPO SA Pipe Flashing	TPO self-adhering cone flashing with a preformed flange and factory applied pressure sensitive tape. Comes with clamping ring. Available in White only	Self-adhering TPO flashing of penetrations of 1"-6" diameters such as pipes, conduit, gas lines, etc.	Various

IB TPO Split Pipe Flashing	TPO no-cone split-pipe flashing with a preformed flange. Available in White, Gray, Tan colors	Heat weldable TPO split-pipe flashing of penetrations of 1"-6" diameters such as pipes, conduit, gas lines, etc.	Various
IB TPO Universal Pipe Flashing	TPO pre-molded universal pipe flashing. Comes with clamping ring. Available in White only.	Heat weldable TPO flashing of penetrations of 1"-6" diameters such as pipes, conduit, gas lines, etc.	6"
IB TPO Square Vent	TPO flashing on a galvanized vent with a square-shaped hood is crafted from coated steel giving a precise color match to the TPO membrane. Available in White, Gray, Tan colors	Heat weldable TPO vent flashing used for non-heated exhaust ventilation	8" square
IB TPO T-Top Roof Vent	TPO flashing on a galvanized vent with a T-shaped hood is crafted from coated steel giving a precise color match to the TPO membrane. Available in White, Gray, Tan colors	Heat weldable TPO vent flashing used for non-heated exhaust ventilation	4", 6", 8" dia.
IB TPO X-Top Roof Vent	TPO flashing on a galvanized vent with a X-shaped hood is crafted from membrane coated steel giving a precise color match to the TPO membrane. Available in White, Gray, Tan colors	Heat weldable TPO exhaust vent flashing used for non-heated exhaust ventilation.	4", 6", 8" dia.
IB TPO Dryer Exhaust Vent	TPO flashing on a heavy-duty two-piece general-purpose roof exhaust vent. Available in White, Gray, Tan colors	Heat weldable TPO exhaust vent flashing used for powered exhaust ventilation	4", 6", 8", 10" dia.
IB TPO Wall Vent Flashing	TPO coated metal with a reinforced TPO membrane flange. Available in White, Gray, Tan colors.	Prefabricated gravity vents commonly used on 90-degree parapet walls to allow free owing air between the vented area and exterior of the structure.	12", 16" 24"
IB TPO Membrane Recover Vent	TPO flashing on a two-way style HPDE vent with a strong cap that is permanently attached. Vent available in White or Black Membrane available in White, Gray, Tan colors.	one-way vent used for recover applications	5" dia.
IB TPO Penetration Curb	Two-piece, rigid molded TPO plastic pan with a rounded base	Used for sealing penetrations and various types of structural supports.	Various
IB TPO Pitch Pan	TPO-clad sheet metal pitch pans	Used for sealing penetrations and various types of structural supports.	Various
IB TPO Clad Metal Scupper	TPO-clad sheet metal scupper	Through-wall drainage scupper	Various
IB TPO Clad Metal Overflow Scupper	TPO-clad sheet metal scupper	Through-wall drainage overflow scupper	Various
IB TPO Retrofit Drain	Clamping ring style roof drain	Primary roof drain	2" To 6"
IB TPO Overflow Retrofit Drain	Clamping ring style overflow roof drain	Overflow roof drain	2" To 6"
IB TPO U-Anchor 2000	Lightweight rooftop attachment anchor consisting of IB TPO target membrane and a U-Anchor 2000 series plate.	Roof top anchor for Adhered systems	each
IB TPO U-Anchor 2400	Lightweight rooftop attachment anchor consisting of IB TPO target membrane and a U-Anchor 2000 series plate.	Roof top anchor for Adhered and Attached systems	each
IB TPO U-Anchor 3400	Lightweight rooftop attachment anchor consisting of IB TPO target membrane and a U-Anchor 3000 series plate.	Roof top anchor for Adhered and Attached systems	each

*Gray and Tan Colors are Special Order and require lead times.

TPO Metal/Termination Bar/Metal Accessories

Product	Description	Use	Size / Unit
IB TPO Clad Metal	IB non-reinforced TPO film laminated to 24-gauge, ASTM A653-09, CS Type B, G90 galvanized sheet metal. Available in White, Gray and Tan colors.	Available in flat sheets to fabricate various metal flashings, drip edge, gravel guard, pitch pans, and scuppers.	4'x10' flat sheets
IB TPO Clad Stainless-Steel Metal	IB non-reinforced TPO film laminated to 24-gauge, SAE 304 stainless steel sheet metal. Available in White only.	Available in flat sheets to fabricate various metal flashings, drip edge, gravel guard, pitch pans, and scuppers.	4'x10' flat sheets
IB Pipe Flashing Clamps	Stainless steel banding clamp	Used to secure pipe flashings. Small clamps are ideal for banding A & B size cones. Large clamps are used for banding C, D, & E Cones.	20.5"/S 40"/L
Foil Tape	Self-adhesive, single sided foil tape	Used over the joints of IB TPO Clad metal	2" x 150'

IB TPO Clad Drip Edge Metal	24-gauge, G90 galvanized clad drip edge metal	Standard metal drip edge profile with an open-hem kick-out at bottom. Available in standard clad finish of white, tan and gray.	2.5" & 4" or custom size available
IB TPO Clad Gravel Stop Metal	24-gauge, G90 galvanized clad gravel stop edge metal	Standard gravel-stop edge profile with a 3/4" rise and an open-hem kick-out at bottom. Available in standard clad finish of white, tan, and gray.	2.5" & 4" or custom size available
TPO Galvanized Metal Cleat	22-gauge, ASTM G53-09, CS Type B, G90 galvanized steel cleat	Standard metal cleat profile with a 1/2" deck flange	2.5" & 4" or custom size available
TPO Stainless Steel Metal Cleat	22-gauge, 304 stainless steel metal cleat	Standard stainless steel metal cleat profile with a 1/2" deck flange	2.5" & 4" or custom size available
IB Drip Edge Profile Flashing	TPO compatible two-piece low profile metal fascia	Available in .040, .050, .063 pre-finished aluminum, 24-ga. or 22-ga. pre-finished steel fascia cover in various color options	3-1/4" x 12' 4-3/4" x 12' 6-1/4" x 12' 7-3/4" x 12'
IB Aluminum Termination Bar	Aluminum termination bar	Used for membrane terminations.	1" x 10'
IB Steel Batten Bar	Heavy duty steel batten bar	Used for membrane terminations on roof decks. 16-gauge Galvalume® coated steel with pre-punched holes at 6" oc.	1" x 10'
IB Polymer Batten Bar	Heavy duty polymer batten bar	Used for membrane terminations on roof decks. Pre-punched holes at 3" oc.	1" x 250'
IB Metal Coping	Parapet coping with anchor clip. Available in aluminum or galvanized steel. Various color options	Includes anchor cleats, coping cover, and fasteners. Splices plates, end caps, and custom corners are sold separately.	12'
IB Pro-Loc Metal Coping	Parapet coping with anchor clip. Available in aluminum or galvanized steel. Various color options	Includes anchor cleats, coping cover, and fasteners. Splices plates, end caps, and custom corners are sold separately.	12'
IB Hi-Wind Metal Coping	Parapet coping with anchor clip. Available in aluminum or galvanized steel. Various color options	Includes anchor cleats, coping cover, and fasteners. Splices plates, end caps, and custom corners are sold separately.	12'
TPO Membrane Adhesive/Accessories			
Product	Description	Use	Size / Unit
IB TPO Water Based Adhesive	Water-based TPO membrane adhesive	Used to adhere IB TPO SM and TPO FB membranes to various horizontal substrates	5 gal. pail
IB TPO Bonding Adhesive	One-part, synthetic polymer-based membrane adhesive, two-sided application for TPO SM membranes.	Used to adhere IB TPO SM membrane to horizontal and vertical surfaces. Not for use with TPO FB membranes.	5 gal. pail
IB TPO LVOC Adhesive	One-part, low VOC, synthetic polymer-based membrane adhesive, two-sided application for TPO SM membranes.	Used to adhere IB TPO SM membrane to horizontal and vertical surfaces. Not for use with TPO FB membranes.	5 gal. pail
IB TPO CA LVOC Adhesive	One-part, low VOC, synthetic polymer-based membrane adhesive, two-sided application for TPO SM membranes.	Used to adhere IB TPO SM membrane to horizontal and vertical surfaces. Not for use with TPO FB membranes.	5 gal. pail
IB TPO Spray Contact Adhesive	One component, spray contact adhesive for TPO membranes	Used to adhere IB TPO SM and TPO FB membranes to various horizontal and vertical substrates including approved ISO and gypsum cover board rated for adhered applications.	45 lb. canister
Rapid Set ECO ₂ Spray Foam	Two-component, low-rise polyurethane foam adhesive	Adhesive designed to adhere TPO FB membranes to various substrates in both new and re-roof applications.	Kit Cannister Pt. 1 (49 lb.) Pt. 2 (43 lb.)
IB TPO Primer	TPO Membrane Primer	One-part membrane primer used to prepare surface for adhering TPO self-adhesive products.	1 gal. can 6 per case
IB Membrane Cleaner	TPO Membrane Cleaner	One-part solvent cleaner used to remove dirt, asphalt or other contaminants from TPO membranes.	1 gal. can 4 per case
IB TPO Clear Cut Edge Sealant	TPO Clear Cut Edge Sealant	Synthetic rubber sealant used to seal cut edges of TPO Membranes where the polyester reinforced scrim is exposed following cutting of the membrane during installation.	16 oz.

Insulation / Thermal Barrier / Cover Boards			
Product	Description	Use	Size / Unit
IB Energy Board II	ASTM C1289, Type II, Class 1, Grade 2 or 3 Polyisocyanurate Board Insulation. Available in various thicknesses.	Polyisocyanurate roof insulation with non-asphaltic, fiber-reinforced organic felt facer.	4' x 4' 4' x 8'
IB Energy Board II Taper	ASTM C1289, Type II, Class 1, Grade 2 or 3 Polyisocyanurate Board Insulation. Available in tapered panels with 1/8", 1/4", and 1/2" per foot.	Tapered polyisocyanurate roof insulation with non-asphaltic, fiber-reinforced organic felt facer.	4' x 4'
IB Energy Board III	ASTM C1289, Type II, Class 2, Grade 2 or 3 Polyisocyanurate Board Insulation. Available in various thicknesses.	Polyisocyanurate roof insulation with inorganic coated glass facer.	4' x 4' 4' x 8'
IB Energy Board III Taper	ASTM C1289, Type II, Class 2, Grade 2 or 3 Polyisocyanurate Board Insulation. Available in tapered panels with 1/8", 1/4", and 1/2" per foot.	Tapered polyisocyanurate roof insulation with inorganic coated glass facer.	4' x 4'
IB HD ISO	ASTM C1289, Type II, Class 4, Grade 1 Polyisocyanurate board with high compressive strength	Used as a cover board in FA, IW, and MA applications.	4' x 4' 4' x 8'
IB Recovery Energy Board III	ASTM C1289, Type II, Class 1, Grade 3 Polyisocyanurate recovery board	1/2" thick closed cell polyisocyanurate foam core panel specifically designed to use in recover and metal retrofit applications.	4' x 4' 4' x 8'
DensDeck® Roof Board	ASTM C1177, Gypsum-based Roof Board	Used as a fire barrier, thermal barrier, or cover board in MA and IW applications. Available in 1/4", 1/2" and 5/8" thicknesses.	4' x 4' 4' x 8'
DensDeck® ProFast™ Prime Roof Board	ASTM C1177, Gypsum-based Roof Board	Used as a cover board in FA, IW, and MA applications. Available in 3/8" thickness.	4' x 8'
DensDeck® Prime Roof Board	ASTM C1177, Gypsum-based Roof Board	Used as a fire barrier, thermal barrier, or cover board in FA, IW, and MA applications. Available in 1/4", 1/2", and 5/8" thicknesses.	4' x 4' 4' x 8'
DensDeck® StormX™ Prime Roof Board	ASTM C1177, Gypsum-based Roof Board. Provides superior hail resistance.	Used as a fire barrier, thermal barrier, or cover board in MA or FA applications. Available in 5/8" thickness.	4' x 4' 4' x 8'
USG Securock® Ultralight Glass-mat Roof Board	ASTM C1177, Gypsum-based Roof Board	Used as a cover board in IW or MA applications. Available in 1/4", 1/2" and 5/8" thicknesses.	4' x 8'
USG Securock® Ultralight Coated Glass-mat Roof Board	ASTM C1177, Gypsum-based Roof Board	Used as a fire barrier, thermal barrier, or cover board in FA, IW, and MA applications. Available in 1/4", 1/2", and 5/8" thicknesses.	4' x 4' 4' x 8'
USG Securock® Gypsum-Fiber Roof Board	ASTM 1278, Gypsum-based Roof Board	Used as a fire barrier, thermal barrier, or cover board in FA, IW, and MA applications. Available in 3/8", 1/2", and 5/8" thicknesses.	4' x 4' 4' x 8'
DEXcell® Glass Mat Roof Board	ASTM C1177, Gypsum-based Roof Board	Used as a fire barrier, thermal barrier, or cover board in IW or MA applications.	4' x 8' 4' x 12'
DEXcell® FA Glass Mat Roof Board	ASTM C1177, Gypsum-based Roof Board	Used as a fire barrier, thermal barrier, or cover board in FA, IW, and MA applications. Available in 1/4", 1/2", and 5/8" thicknesses.	4' x 4' 4' x 8'
Insulation Adhesive/Insulation Adhesive Accessories			
Product	Description	Use	Size / Unit
Rapid Set Adhesive	Two-component, low-rise polyurethane foam adhesive	Adhesive designed to adhere insulation and cover boards to various substrates	1.5 L cartridge
Rapid Set PG Foam	Two-component, low-rise polyurethane foam adhesive	Adhesive designed to adhere insulation and cover boards to various substrates	5 gal 15 gal (ea.) 50 gal (ea.)
Rapid Set ECO ₂ Spray Foam	Two-component, low-rise polyurethane foam adhesive	Adhesive designed to adhere insulation and cover boards to various substrates and as fleece back membranes to various substrates in both new and re-roof applications.	Kit Cannister Pt. 1 (49 lb.) Pt. 2 (43 lb.)
Olybond500® Adhesive Fastener	Two-component, low-rise polyurethane foam adhesive	Adhesive designed to adhere insulation and cover boards to various substrates	5 gal
Olybond500® Cannister	Two-component, low-rise polyurethane foam adhesive	Adhesive designed to adhere insulation and cover boards to various substrates	Kit Cannister Pt. 1 (48 lb.) Pt. 2 (44 lb.)
TruFast Roofing Adhesive	Two-component, low-rise polyurethane foam adhesive	Adhesive designed to adhere insulation and cover boards to various substrates	1.5 L cartridge

TruFast Roofing Adhesive Tanks	Two-component, low-rise polyurethane foam adhesive	Adhesive designed to adhere insulation and cover boards to various substrates	Kit Cannister Pt. A (59 lb.) Pt. B (56 lb.)
APOC Polyset Commercial Roof Adhesive	Two-component, low-rise polyurethane foam adhesive	Adhesive designed to adhere insulation and cover boards to various substrates and as fleece back membranes to various substrates in both new and re-roof applications.	Kit Cannister 27.7 lb. kit 44 lb. (ea.)

Separation Sheets

Product	Description	Use	Size / Unit
IB Separator Sheet	Lightweight reinforced synthetic separation sheet	Divorcing layer used between IB membranes and incompatible or contaminated materials and surfaces	5' 10" x 515'
IB Poly Separator Sheet	Standard duty spun bond polyester roll	Divorcing layer used between IB membranes and incompatible or contaminated materials and surfaces	7' 6" x 360'
IB HD Poly Separator Sheet	Heavy duty spun bond polyester roll	Divorcing layer used between IB membranes and incompatible or contaminated materials and surfaces	7' 6" x 150'
Atlas Fire Sheet 10	Fire resistant separation sheet	Divorcing layer and fire barrier used for combustible roof decks	4' x 250'

Vapor Retarders

Product	Description	Use	Size / Unit
<i>IB</i> Barrier™ SA Membrane	31-mil SBS, self-adhered vapor retarder	Vapor retarder designed for installation over various roof decks or primed gypsum cover boards	3.75' x 134'
<i>IB</i> Barrier™ FG SAR	47-mil SBS, self-adhered vapor retarder	Vapor retarder designed for installation over various roof decks or primed gypsum cover boards	3.28' x 105'
<i>IB</i> Barrier™ Primer	Primer used in conjunction with <i>IB</i> Barrier SA and <i>IB</i> Barrier SA 106 membrane	Used to prime steel, plywood, or concrete roof decks	5 gal. pail
<i>IB</i> Barrier™ Primer LV	LEED compliant primer used in conjunction with <i>IB</i> Barrier SA <i>IB</i> Barrier SA 106 membrane	Used to prime steel, plywood, or concrete roof decks	5 gal. pail
<i>IB</i> Barrier™ XP SA Membrane	10 mil, synthetic non-permeable, self-adhered vapor retarder	Vapor retarder designed for installation over various roof decks or primed gypsum cover boards	60" x 100'
<i>IB</i> Barrier™ SA 106	106-mil, SBS self-adhered vapor retarder	Vapor retarder designed for installation over various roof decks or primed gypsum cover boards	3.28' x 49.2'
<i>IB</i> Barrier™ 90G TG SBS	120-mil SBS glass-reinforced membrane	Vapor retarder designed for installation over various roof decks or primed gypsum cover boards	3.28' x 49.2'
<i>IB</i> Barrier™ 120G TG SBS	120-mil SBS glass-reinforced membrane	Vapor retarder designed for installation over various roof decks or primed gypsum cover boards	3.28' x 32.7'
<i>IB</i> Barrier™ 120P TG SBS	120-mil SBS polyester-reinforced membrane	Vapor retarder designed for installation over various roof decks or primed gypsum cover boards	3.28' x 32.7'

Fasteners / Plates

Product	Description	Use	Size / Unit
IB SD #12 Insulation Fastener	#12 Insulation Fastener, #3 Phillips Drive	Used to secure insulation and separation materials	Various lengths
IB HD #14 Roofing Fastener	#14 Heavy-Duty Roofing Fastener, #3 Phillips Drive	Used as a membrane and/or insulation fastener	Various lengths
IB XHD #15 Roofing Fastener	#15 Extra Heavy-Duty Roofing Fastener, #3 Phillips Drive	Used as a membrane and/or insulation fastener	Various lengths
IB #12 Purlin Fastener	#12 Purlin Fastener, #3 Square Drive, Pancake Head	Used as a membrane and/or insulation fastener into steel purlins	Various lengths
#14 Stainless Roofing Fastener	#14 Heavy-Duty Stainless Steel Roofing Fastener, #3 Phillips Drive	Used as a membrane and/or insulation fastener	Various lengths
CD-10 Concrete Fastener	Hammer-in Concrete Nail, Pan Head	Used as a membrane and/or insulation fastener into structural concrete decks	Various lengths
Polymer GypTec® Fastener	Glass-filled Nylon Auger Fastener, 1" Head	Used as a membrane and/or insulation fastener into gypsum or tectum decks in	Various lengths

		conjunction with compatible 2" or 3" GypTec® plate.	
IB 3" Insulation Plate	Galvalume Insulation Plate	Used with IB roofing fasteners to secure insulation and separation materials	3" Dia.
Fasteners / Plates (continued)			
Product	Description	Use	Size / Unit
IB Insulation Plate	Galvalume Insulation Plate	Used with IB roofing fasteners to secure insulation and separation materials	3" Dia.
IB 2" Barbed Seam Plate	Galvalume 2" Barbed Seam Plate	Used in in-seam MA roofing assemblies	2" Dia.
IB 2" Seam Plate	Galvalume 2" Barbed Seam Plate	Used in in-seam MA roofing assemblies	2" Dia.
IB 2-3/8" Barbed Seam Plate	Galvalume 2-3/8" Barbed Seam Plate	Used in in-seam MA roofing assemblies	2-3/8" Dia.
IB 2-3/8" Seam Plate	Galvalume 2-3/8" Barbed Seam Plate	Used in in-seam MA roofing assemblies	2-3/8" Dia.
IB TPO 3" IW Insulation Plate	3" TPO Coated Plate	Used as an insulation plate in conjunction with SD #12, HD #14, XHD #15, or #12 Purlin Fasteners when using the isoweld® induction device	3" Dia.
3-1/2" Cardboard Spacer FI-Pad	3-1/2" Cardboard Spacer	Used in combination with an isoweld® plate when installing thermoplastic roof membrane over EPS or XPS insulation	3-1/2"
RhinoBond® TPO Plate	3" TPO Coated Plate	Used as an insulation plate in conjunction with SD #12, HD #14, XHD #15, or #12 Purlin Fasteners when using the RhinoBond® induction device	3" Dia.
4" RhinoBond® Cardboard Disc	4" Cardboard Disc	Used in combination with an RhinoBond® plate when installing thermoplastic roof membrane over EPS or XPS insulation	4"
2" GypTec® Plate	2" Galvalume Barbed Seam Plate	Used in in-seam MA roofing assemblies in conjunction with the GypTec® Fastener	2"
3" GypTec® Plate	3" Galvalume Insulation Plate	Used as an insulation plate in conjunction with the GypTec® Fastener	3"
Zac Anchors	Termination Bar /Counter Flashing Anchor	Designed to secure termination bar, counter flashing, and various metal flashings to wood, masonry / concrete, and steel.	1-3/8"
Zinc Nailin Anchors	Termination Bar /Counter Flashing Mushroom Head Anchor	Designed to secure termination bar, counter flashing, and various metal flashings to wood, masonry / concrete, and steel.	Various lengths
Sealants			
Product	Description	Use	Size / Unit
IB Sealer	Single component, 80% solids moisture-curing and self-leveling sealant. Available in gray.	Multi-purpose sealant used in vertical terminations, vent openings, pipes, and as a fluid applied filler for penetrations in pitch pans.	2.5-gal pail 5-gal pail
IB Seal-NT	Single component low modulus, solvent-free Silyl Modified Polyether Sealant. Available in white, gray, or black.	Multi-purpose sealant used in vertical terminations, vent openings, pipes.	10.1 oz tube
IB Water Stop	Butyl-based mastic designed to seal membrane to a variety of surfaces	Sealant used in compression details such as vertical terminations, vent opening, pipes, and drain details	11 oz tube
M-1 Sealant	Multi-purpose sealant used various conditions and used in conjunction with IB Clad Pitch Pans	Primarily used to prime penetrations to be treated with One-Part Pourable Sealant in pitch pans	10.1 oz tube
One-Part Pourable Sealant	One-part pourable sealant for use in pitch pans	Used as a fluid applied flashing for penetrations in pitch pans	2L pouch