



NOTES:

1. SEALANT AND CAULKING REQUIRE PERIODIC OWNER MAINTENANCE.
2. SECURE METAL EDGE AND NAILER TO MEET PROJECT WIND LOADS BUT NO LESS THAN WITH STAINLESS STEEL NAILS AT 4" O.C. STAGGERED OR WITH IB HD #14 FASTENERS AT 12" O.C.
3. CLEAN AND WIPE METAL EDGING PRIOR TO INSTALLATION.
4. IB TPO SA COVER TAPE, OR IB TPO HW-SA COVER TAPE AS APPLICABLE. SEE RELATED APPLICATION ON CLAD DRIP EDGE DETAIL.
5. CONFORMS TO ANSI/SPRI ES-1 WHEN USED IN ACCORDANCE WITH TESTED ASSEMBLY.
6. 20 YEAR, 90 MPH WIND WARRANTY AVAILABLE WITH INCLUSION IN IB TOTAL SYSTEM WARRANTY BASED ON MEMBRANE THICKNESS AND WARRANTY PROGRAM
7. AVAILABLE IN SEVERAL STANDARD AND SELECT COLORS.

Scale: NTS	Detail Name: IB Drip Edge Profile with TPO Membrane	Detail Number: T-PE-22
----------------------	--	---

Submitted By: Address: Telephone:	Project: Address:
--	-----------------------------