



NOTES:

1. INSTALLATION OF EXPANDABLE SEAL REQUIRES USE OF A PRO-SEAL SCREWDRIVER TO CREATE A WATER-TIGHT CONNECTION TO EXISTING PREPARED DRAIN PIPE. 2" MODEL DRAINS ARE SUPPLIED WITH ALTERNATE EXPANDABLE FOAM COMPRESSION SEAL. REMOVE SEAL RETENTION TAPE PRIOR TO INSTALLATION.
2. FASTEN DRAIN FLANGE 12" O.C. WITH MINIMUM OF 4 FASTENERS PER DRAIN USING IB FASTENERS.
3. MEMBRANE DRAIN LINERS ARE NOT ELIGIBLE FOR AN IB TOTAL ROOF SYSTEMS WARRANTY.
4. RE-ROOF APPLICATIONS: REMOVE EXISTING LEAD, FLASHING MATERIAL & ENSURE THE DRAIN PIPE IS COMPLETELY CLEAN AND FREE OF ASPHALT OR OTHER CONTAMINANTS.
5. INSPECT CLAMPING RING AND BOLTS UPON INSTALLATION TO ENSURE UNIFORM COMPRESSION AND A WATERTIGHT SEAL IS PRESENT BETWEEN THE DRAIN FLANGE AND TARGET SHEET.
6. OVERFLOW DRAIN INSTALLATION REQUIRES USE OF ALTERNATE 2-INCH, NO-CUT OUT OVERFLOW CLAMPING RING.

Scale: NTS	Detail Name: IB TPO Retrofit Overflow Drain	Detail Number: T-RD-05
Submitted By: Address: Telephone:		Project: Address: