



**NOTES:**

1. SINGLE COURSE WALL FLASHING MAXIMUM HEIGHTS:
  - A. 60" ABOVE ROOF DECK.
  - B. FOR WALLS EXCEEDING MAXIMUM HEIGHTS REFER TO ADHERED TALL WALL DETAIL.

**APPROVED SUBSTRATE / SEPARATION: NEW CONSTRUCTION - FULLY ADHERED**

1. ADHERED WALLS: INSTALL MEMBRANE IN IB TPO BONDING ADHESIVE AT APPROVED APPLICATION RATE
2. INSTALLED COVERAGE (50% TO SUBSTRATE ALLOW TO DRY WITH REMAINING 50% TO BACK OF SHEET, INSTALL WHILE TACKY)
  - SECURE FLASHINGS AND METAL WORK IN ACCORDANCE WITH IB SPECIFICATIONS AND FLASHING SECUREMENT TABLE.
  - 1/2" PLYWOOD, 7/16" OSB, 1/2" APPROVED GYPSUM COVER BOARD, POURED / PRECAST CONCRETE, OR CEMENT BLOCK / MASONRY WALLS.
  - SEALANTS AND CAULKING REQUIRE PERIODIC OWNER MAINTENANCE.
  - FULLY ADHERED RECOVER OVER APPROVED EXISTING WALL AND BASE FLASHINGS:
  - FULL SEPARATION REQUIRED WITH MINIMUM 1/2" PLYWOOD, 1/4" APPROVED GYPSUM COVER BOARD, OR 7/16" OSB.
  - REFER TO FT AND/OR PT DETAILS FOR APPROVED FLASHING AND PARAPET WALL TERMINATIONS.

Scale: NTS	Detail Name: <b>Adhered TPO Wall</b>	Detail Number: <b>T-WD-01</b>
Submitted By: Address: Telephone:		Project: Address: